Tank Geometry and Volume Propellant Requirements January 1997

Table 1
Tank Volume Requirements

Requirement	RP-1 Tank	Combined LOX Tanks	
Usable Mass	8647 lbm	18852	
Loaded Mass	8939 lbm	21015 lbm	
Density (on ground)	50.5 lbs/ft^3	71.25 lbs/ft^3	
Residual Propellant	292 lbm	266 lbm	
Ullage (on ground)	2 Percent of Total Volume	2 Percent of Total Volume	
Loss of Volume Due to	0.3 Percent of Total Volume	0.3 Percent of Total Volume	
Internal Hardware			
Boil-Off	Not Applicable	1285 lbm	
Chill Down	Not Applicable	612 lbm	
Loss of Volume Due to	Not Applicable	1.2 Percent of Total Volume	
Contraction			
Tank O.D	62.00 Inches	54.00 Inches	
Wall Thickness	0.10 Inches	0.125 Inches	
Dome Height	0.707R	0.707R	
Access Door Radius	10.00 Inches	10.00 Inches	
Total Required Volume	181.18 ft ^3	305.64 ft^3	

Table 2 LOX Tank as Designed Volumes

Item	Spread Sheet	IDEAS Model	
Forward Tank, Forward	39.20	39.10	
Compartment			
Forward Tank, Middle	39.20	39.10	
Compartment			
Forward Tank, Aft	45.29	46.00	
Compartment			
Forward Tank Total	123.69	124.20	
Aft Tank, Forward	44.68	44.57	
Compartment			
Aft Tank, Second to	44.68	44.57	
Forward Compartment			
Aft Tank, Second to Aft	44.68	44.57	
Compartment			
Aft Tank, Aft Compartment	47.01	47.71	
Aft Tank Total	181.05	181.44	
Combined LOX Tanks	304.74	305.64	

Table 2 lists the calculated volumes for the LOX design in Figure 2 and 3. Two methods, a spread sheet and an IDEAS 3-D model were used to calculate the volumes. As listed in Table 2, the two methods are within 0.4 percent of each other.

Table 3
RP-1 Tank as Designed Volumes

Item	Spread Sheet	IDEAS Model
RP-1 Tank, Forward	61.95	61.86
Compartment		
RP-1 Tank, Middle	61.95	61.86
Compartment		
RP-1 Tank, Aft	65.01	65.17
Compartment		
RP-1 Tank Total	188.91	188.90

Table 3 lists the calculated volumes for the RP-1 design in Figure 4. Two methods, a spread sheet and an IDEAS 3-D model were used to calculate the volumes. The two methods provide nearly identical results, however, the design is 4.3 percent larger than the requirement. Due to the uncertainties with the LOX loading, the RP-1 tank structure will not be modified at this time.

Table 4
Mass Properties for the LOX and RP Tanks

Item	RP-1 Tank	Forward LOX Tank	Aft LOX Tank
Total Load Propellant	8939 lbs	8540 lbs	12475 lbs
(Total Usable Propellant)	8647 lbs	7661 lbs	11191 lbs
Tank Structure	204.7 lbs	419.9 lbs	564.5 lbs
	0480 8 11	0050 0 11	12020 5 11
Total	9179.7 lbs	8959.9 lbs	13039.5 lbs
Predicted c.g. (Vehicle Station Location)	325.8	461.4	608.2

The current mass properties of the tanks are defined in Table 4 for each of the tanks. The mass properties are for the fully loaded, on the ground condition. The c.g. is assumed to be half way between the attachment bulkheads. Note, the mass of the structure does not include any components attached to the tank, the close-out doors, or the attachment of the tank to the bulkhead.